

BEST AVAILABLE COPY

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

IN THE CLAIMS

Please amend the claims as follows.

1. (Cancelled).
2. (Currently Amended) A pipelined microprocessor capable of detecting an instruction that loads data from a first memory location that was previously stored to, wherein the instruction is detected without requiring computation of an external memory address of said first memory location for the instruction, and wherein the instruction is detected by identifying an identical offset address value and an identical base address value associated with the instruction and another instruction that previously stored data to the first memory location.
3. (Previously Presented) A pipelined microprocessor as claimed in Claim 2 wherein said pipelined microprocessor is capable of detecting an instruction that stores data into a second memory location that was previously read from without computing an external memory address of said second memory location.
4. (Previously Presented) A pipelined microprocessor as claimed in Claim 2 wherein said pipelined microprocessor is capable of detecting instructions that load data from identical memory locations that were previously stored to without computing external memory addresses of said identical memory locations.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

5. (Previously Presented) A pipelined microprocessor as claimed in Claim 2 wherein said pipelined microprocessor is capable of detecting instructions that store data into identical memory locations that were previously read from without computing external memory addresses of said identical memory locations.

6. (Previously Presented) A pipelined microprocessor as claimed in Claim 4 wherein said pipelined microprocessor is capable of examining symbolic structure of said instructions that load data from identical memory locations that were previously stored to, and capable of detecting said instructions that load data from identical memory locations by examining said symbolic structure.

7. (Previously Presented) A pipelined microprocessor as claimed in Claim 5 wherein said pipelined microprocessor is capable of examining symbolic structure of said instructions that store data into identical memory locations that were previously read from, and capable of detecting said instructions that store data into identical memory locations by examining said symbolic structure.

8. (Previously Presented) A pipelined microprocessor as claimed in Claim 6 wherein said pipelined microprocessor is capable of detecting said instructions that load data from identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

9. (Previously Presented) A pipelined microprocessor as claimed in Claim 7 wherein said pipelined microprocessor is capable of detecting said instructions that store data into identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor.

10. (Previously Presented) A pipelined microprocessor as claimed in Claim 6 wherein said pipelined microprocessor comprises:

an instruction decode stage capable of detecting said instructions that load data from identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor; and

a bypass element capable of sending a bypass signal to an instruction execution stage of said pipelined microprocessor that indicates that said instructions refer to an identical memory location.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

11. (Previously Presented) A pipelined microprocessor as claimed in Claim 7 wherein said pipelined microprocessor comprises:

an instruction decode stage capable of detecting said instructions that store data into identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor; and

a bypass element capable of sending a bypass signal to an instruction execution stage of said pipelined microprocessor that indicates that said instructions refer to an identical memory location.

12. (Currently Amended) A method for operating a pipelined microprocessor, said method comprising:

detecting in said pipelined microprocessor an instruction that loads data from a first memory location that was previously stored to, wherein the instruction is detected without requiring computation of an external memory address of said first memory location for the instruction, and wherein the instruction is detected by identifying an identical offset address value and an identical base address value associated with the instruction and another instruction that previously stored data to the first memory location.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

13. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 12, said method further comprising:

detecting in said pipelined microprocessor an instruction that stores data into a second memory location that was previously read from without computing an external memory address of said second memory location.

14. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 12, said method further comprising:

detecting in said pipelined microprocessor instructions that load data from identical memory locations that were previously stored to without computing external memory addresses of said identical memory locations.

15. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 12, said method further comprising:

detecting in said pipelined microprocessor instructions that store data into identical memory locations that were previously read from without computing external memory addresses of said identical memory locations.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

16. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 14, said method further comprising:

examining in said pipelined microprocessor symbolic structure of said instructions that load data from identical memory locations that were previously stored to; and

detecting said instructions that load data from identical memory locations by examining said symbolic structure.

17. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 15, said method further comprising:

examining in said pipelined microprocessor symbolic structure of said instructions that store data into identical memory locations that were previously read from; and

detecting said instructions that store data into identical memory locations by examining said symbolic structure.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

18. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 16, said method further comprising:

detecting in an instruction decode stage of said pipelined microprocessor said instructions that load data from identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor; and

sending a bypass signal from a bypass element to an instruction execution stage of said pipelined microprocessor wherein said bypass signal indicates that said instructions refer to an identical memory location.

19. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 17, said method further comprising:

detecting in an instruction decode stage of said pipelined microprocessor said instructions that store data into identical memory locations by identifying an identical offset address value from an identical base address value in a register within said pipelined microprocessor; and

sending a bypass signal from a bypass element to an instruction execution stage of said pipelined microprocessor wherein said bypass signal indicates that said instructions refer to an identical memory location.

DOCKET NO. 98-MET-069C1
SERIAL NO. 09/443,160
PATENT

20. (Currently Amended) A method for operating a pipelined microprocessor, said method comprising:

detecting a first instruction that stores data to a first memory location, said first instruction comprising syntax for computing an effective address for said first memory location;

detecting a second instruction that loads data from a second memory location, said second instruction comprising syntax for computing an effective address for said second memory location;

determining said syntax for said first instruction and said syntax for said second instruction;

using said syntax for said first instruction and said syntax for said second instruction to determine a relationship between said first memory location and said second memory location, without requiring computation of said effective address for said first memory location and without requiring computation of said effective address for said second memory location, wherein using said syntax comprises identifying identical offset address values and identical base address values associated with the instructions; and

using said relationship to determine whether to perform one of said first instruction and said second instruction.

21. (Previously Presented) A method for operating a pipelined microprocessor as claimed in Claim 20 wherein said syntax for said first instruction and said syntax for said second instruction refer to an identical memory location.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.